

Multi-Sensor

It can be used with your THINKY Mixer

Material temperature can be measured in real time

Rotational speed can be measured in real time

Bluetooth connectivity for data logging via PC



The picture taken with ARV-310P

■ Specification (Multi-Sensor)


Model		MS-150ML	MS-300ML	MS-550ML
Container		150 ml HDPE container	300 ml HDPE standard container	550 ml ,650 ml HDPE container
Temperature	Sensor Type	Non contact infrared thermometer		
	Measuring range	+0.0 °C ∼ +79.9 °C		
	Resolution (Minimum)	0.1 ℃		
Rotation	Sensor Type	angular velocity measuring method		
	Measuring range	200~2000 rpm *Not compatible with defoaming mode (Lower speed rotation)		
	Resolution (Minimum)	1rpm		
Power Supply		Multi sensor : Coin cell (Lithium Battery CR2450) Bluetooth receiver : USB		
Battery life		100 hour		
Unit Dimensions		The height of standard 300 ml container + 27 mm		
Weight		Approx, 100 g (Including 150 ml container)	Approx. 135 g (Including 300 ml standard container)	Approx. 155 g (Including 550 ml container)

* Product specifications are subject to change without prior notice.

PC

■ Specification (Software)

os	Windows7, 8, 10(32 bit, 64 bit)	
Display Items	Temperature, deg/s, Rotational speed in RPM, Remaining battery power	
Log Data	Can be exported to CSV file	



Display image

Supported Models

ARE-250CE / ARE-310 / ARE-500 / ARE-500CE / ARE-501 / ARV-310 / ARV-310CE / ARV-310P / ARV-310PCE /ARV-310LED / ARV-310LEDCE / SR-500 / SR-500CE

Product appearance/specifications may change without notice.

THINKY CORPORATION

https://www.thinkymixer.com/en-gl/

Head quarters: 2-16-2 Sotokanda, Chiyoda-ku, Tokyo 101-0021

Phone: +81-3-5207-2713 Fax: +81-3-5289-3281

THINKY USA Inc.: 23151 Verdugo Drive, Suite 112 Laguna Hills, CA 92653, USA

THINKY CHINA: East building, HaiAn Kafunuo Mansion, Shennan road,

Qianhai road, Nanshan district, Shenzhen

^{*} The accuracy of sensor may decreased depending on operating environment.